

DORTON

SOLAR DECKING LIGHT

USER GUIDE



Ensure your solar panel is South facing or as near as possible



Clean your solar panel from time to time



Do NOT place your solar panel in shaded areas.



Do NOT charge behind glass


Thank you for choosing the the Dorton Solar Decking Light. Please read these instructions carefully before using your light.

Installation

Before you take the time to recess your Dorton Solar Decking Light, it is important to think about the amount of light it will receive each day. Position the light in an area that gets good sunlight, which is not obstructed by trees, foliage, buildings, fences, outdoor furniture, or the shadows these can create. For best results, mount the light horizontally. Failure to do this could result in you making alterations to your decking or patio for a light that will not work well in that location.

1. Create an 116mm diameter round hole in your chosen area of installation.
2. Place the lamp unit in the hole.
3. The light is locked from the factory for safe shipment,

so you should put the light under sunlight to activate it. If users would like to lock (turn off) the light, you can put the solar panel side down. Once you have put the solar panel face down, it needs to be re-activated by putting it under sunlight again.



How it works

During daylight hours, the sun charges the battery in the Solar Round Decking Light, which then powers the light after dark. The Dorton Solar Decking Light illuminates automatically at dusk and switches itself off automatically at dawn. Should you wish to turn the light off, it must be turned upside down (or panel face down).

Please note

It is essential that the light casing is completely flush to your chosen surface once installed. If the light sits above ground level it can become a trip hazard. Please take extreme care before creating a hole in your property. There may be hazards underground such as cabling or pipes which could cause severe injury or property damage if disturbed during the installation process. If unsure, The Solar Centre advises seeking the advice/services of a professional when installing the Dorton Solar Decking Light.

Troubleshooting

Please ensure that there are no nearby light sources shining on the solar panel after dark. These could be bright indoor/outdoor lights from your property, neighbours, or street lights.

If you are unsure, take the light indoors and test it in a dark room, or by covering the solar panel with an opaque object, such as your hand, or a kitchen towel.

If you are encountering any problems with your light, often you can resolve this yourself by following our troubleshooting guide. If the light has a solar panel in a poor location it will struggle to work, but that doesn't mean there is a fault with the unit. Please remember that the light may arrive with some charge, and will likely work for a few days, even if the solar panel is poorly located. Please try the troubleshooting tips below before contacting your retailer.

Recharge procedure

1. Double check the location of your solar panel to ensure it is in a clear position and as South-facing as possible.
2. Turn the light off and leave it to recharge for 3-5 days, ensuring at least one sunny day has passed.
3. After 3-5 days return to the light and turn it back on.
4. If your light still does not illuminate after dark, please contact your retailer.

Maintenance

Clean the surface of the solar panel and light lens with a soft, slightly moistened cloth. Do not use corrosive cleansing agents or chemical solutions as these may damage surfaces and impair operation. Keep the solar panel free of dirt, debris and snow.

Safety Instructions

The Solar Centre assumes no liability for any damage resulting from the use of this product, not do we assume liability for any damage to property or personal injury caused by improper use or failure to observe these instructions.

Unauthorized conversion and/or modification of the unit may be dangerous and will invalidate your warranty. To avoid damage to sight, do not look directly at the light source. This device is not a toy and should be kept out of the reach of children. Do not submerge the device in water or expose it to extreme temperatures (less than -25°C or higher than 50°C).

For customer support
please contact:
The Solar Centre Ltd
44-46 Coldharbour Lane
Harpenden
Hertfordshire
AL5 4UN

T: 01727743200
W: www.solarcentre.co.uk
E: info@thesolarcentre.co.uk

