SAFETY DATA SHEET SANDERSON

Date of issue/Date of revision

: 10 October 2024

Version : 1.26

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

| Product name | : SANDERSON Water Based Eggshell |
|----------------------------------|----------------------------------|
| Product code | : 00389122 |
| Product type | : Liquid. |
| Other means of identification | : Not available. |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Professional painting, indoor brush/roller Professional spray painting, indoor (with or without respiratory protection)

Product use

: Consumer applications, Professional applications, Used by spraying, Application by non spray methods..

1.3 Details of the supplier of the safety data sheet

ÌÜdaa)å^¦•[}ÁÖ^•āt}ÁÕ¦[č]ÁÓ¦aa)å•ÁŠā[ãz∿å X[^•^^Á?[č•^ Ùaa)å^¦•[}•ÁŠaa)^ Š[}å[}ÊAVS ÉIIÁÇEDÁGEHÁIÍÏÁÍÌÎG

e-mail address of person[°] responsible for this SDS

enquiries@sandersondesigngroup.com

1.4 Emergency telephone number

Supplier

+44 (0) 203 457 5862

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to UK CLP/GHS Skin Sens. 1, H317

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



Warning

Signal word Hazard statements <u>Precautionary statements</u> General

- May cause an allergic skin reaction.
- : Keep out of reach of children. If medical advice is needed, have product container or label at hand.

| Code | : 00389122 | Date of issue/Date of revision | : 10 October 2024 | | |
|-----------------------------------|------------|--------------------------------|-------------------|--|--|
| SANDERSON Water Based Eggshell | | | | | |
| CECTION 2. Honordo identification | | | | | |

SECTION 2: Hazards identification

| Prevention | : | Wear protective gloves. Avoid breathing vapour. |
|---|----|--|
| Response | : | IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. |
| Storage | : | Not applicable. |
| Disposal | : | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| | | ₱102, P101, P280, P261, P302 + P352, P333 + P313, P362 + P364, P501 |
| Supplemental label elements | : | Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable. |
| Special packaging requirem | en | <u>ts</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : | None known. |
| | | |

SECTION 3: Composition/information on ingredients

| F (2-benzisothiazol-3(2H)-one EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 pyrithione zinc REACH #: 01-2119511196-46 EC: 220-120-9 | <0.10 | Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) Acute Tox. 3, H301 Acute Tox. 2, H330 | [1] |
|--|---------|--|-----|
| 01-2119511196-46 | <0.025 | Acute Tox. 3, H301 | [1] |
| CAS: 13463-41-7 Index: 613-333-00-7 | | Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10) | |
| 2-methylisothiazol-3(2H)-one REACH #: 01-2120764690-50 EC: 220-239-6 CAS: 2682-20-4 Index: 613-326-00-9 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) | [1] |

| Code : 00389122 SANDERSON Water Based Eggshell | Date of issue/Date of revision | : 10 October 2024 | | | |
|---|--------------------------------|--|--|--|--|
| SECTION 3: Composition/information on ingredients | | | | | |
| | | Aquatic Chronic 1, H410 (M=1) EUH071 | | | |

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Inhalation Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. : If swallowed, seek medical advice immediately and show the container or label. Keep Ingestion person warm and at rest. Do NOT induce vomiting. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

| Potential acute health effects | | |
|--------------------------------|----|---|
| Eye contact | ; | No known significant effects or critical hazards. |
| Inhalation | : | No known significant effects or critical hazards. |
| Skin contact | : | May cause an allergic skin reaction. |
| Ingestion | : | No known significant effects or critical hazards. |
| Over-exposure signs/sympto | on | <u>15</u> |
| Eye contact | : | No specific data. |
| Inhalation | : | No specific data. |
| Skin contact | : | Adverse symptoms may include the following: irritation redness |
| Ingestion | ; | No specific data. |
| 4.3 Indication of any immedia | te | medical attention and special treatment needed |
| Notes to physician | : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : | No specific treatment. |

| Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758 | | | | | | |
|--|---|--|--|--|--|--|
| Code : 00389122 SANDERSON Water Based B | Date of issue/Date of revision : 10 October 2024 Eggshell •••••••••••••••••••••••••••••••••••• | | | | | |
| SECTION 5: Firefigh | SECTION 5: Firefighting measures | | | | | |
| 5.1 Extinguishing media | | | | | | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | | | | | |
| Unsuitable extinguishing media | : None known. | | | | | |
| 5.2 Special hazards arising f | rom the substance or mixture | | | | | |
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. | | | | | |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon oxides metal oxide/oxides | | | | | |
| 5.3 Advice for firefighters | | | | | | |
| Special protective actions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. | | | | | |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents. | | | | | |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel Mo action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through split material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". E.2 Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environments pollution (sewers, waterways, soil or air). Methods and material for containment and cleaning up Stop leak if without risk. Move containers from spill area. Dilute with water and mo up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. | English (GB) | United Kingdom (UK) 4 | /15 |
|---|-------------------|---|-----|
| personnelEvacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".6.2 Environmental precautions: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmenta pollution (sewers, waterways, soil or air).6.3 Methods and material for containment and cleaning up Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mo up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Containment and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Containment and place in container for | | See Section 8 for information on appropriate personal protective equipment. | |
| personnelEvacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".6.2 Environmental precautions: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmenta pollution (sewers, waterways, soil or air).6.3 Methods and material for containment and cleaning up Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mo up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. | Large spill | from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and | |
| personnel Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). | Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and moup if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. | р |
| personnel Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | precautions | and sewers. Inform the relevant authorities if the product has caused environment pollution (sewers, waterways, soil or air). | |
| personnelEvacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. | | information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | |
| | For non-emergency | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation i | S |

Code : 00389122 Date

Date of issue/Date of revision

: 10 October 2024

SANDERSON Water Based Eggshell

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

No exposure limit value known.

No exposure indices known.

Recommended monitoring procedures

ring : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Code : 00389122

Date of issue/Date of revision

: 10 October 2024

SANDERSON Water Based Eggshell

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Туре | Exposure | Value | Population | Effects |
|---|--|--|---|---|---|
| pyrithione zinc 2-methylisothiazol-3(2H)-one | DNEL DNEL DNEL DNEL DNEL DNEL | Long term Dermal Long term Dermal Long term Inhalation Long term Inhalation Long term Dermal Long term Inhalation | 0.345 mg/kg bw/day 0.966 mg/kg bw/day 1.2 mg/m ³ 6.81 mg/m ³ 0.01 mg/kg bw/day 0.021 mg/m ³ | General population Workers General population Workers Workers General population | Systemic Systemic Systemic Systemic Local |
| | DNEL DNEL DNEL DNEL DNEL | Long term Inhalation Long term Oral Short term Inhalation Short term Inhalation Short term Oral | 0.021 mg/m ³ 0.027 mg/kg bw/day 0.043 mg/m ³ 0.043 mg/m ³ 0.053 mg/kg bw/day | Workers General population General population Workers General population | Local Local |

PNECs

No PNECs available

8.2 Exposure controls

| Appropriate engineering controls | : | Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
|---|-----|---|
| Individual protection measu | res | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection <u>Skin protection</u> | : | Safety glasses with side shields. |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. nitrile rubber, butyl rubber, PVC, Viton® |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | - | Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3 |

| Code | : 00389122 | Date of issue/Date of revision |
|------|------------|--------------------------------|
| | | |

: 10 October 2024

SANDERSON Water Based Eggshell

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| <u>Appearance</u> | | | | | |
|--|--------------|---------------------------------------|--|--------|--|
| Physical state | : Liquid. | | | | |
| Colour | : Variou | s | | | |
| Odour | : Odourless. | | | | |
| Odour threshold | : Not av | : Not available. | | | |
| Melting point/freezing point | : | · · · · · · · · · · · · · · · · · · · | | | |
| Initial boiling point and boiling range | : >37.78 | : >37.78°C (>100°F) | | | |
| Flammability (solid, gas) | : liquid | | | | |
| Upper/lower flammability or explosive limits | : Not av | ailable. | | | |
| Flash point | : Closed | l cup: Not app | licable. | | |
| Auto-ignition temperature | : | | | | |
| Ingredient name | | °C | °F | Method | |
| sobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | | 393 | 739.4 | | |
| рH | : 8.5 | | | | |
| Viscosity | | | perature): Not avai nperature): Not ava | | |

Solubility(ies)

| | Media | Result | | | |
|---|----------------------------|-------------------|--|--|--|
| | cold water | Partially soluble | | | |
| Ν | Miscible with water : Yes. | | | | |

Kinematic (40°C): >21 mm²/s

Partition coefficient: n-octanol/ : Not applicable.

ŝ

water

Vapour pressure

| | Va | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|--------------------------|--------|-------------------------|---|----------------|-------------------------|--------------------|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method | |
| water | 17.5 | 2.3 | | | | | |
| Relative density | : 1.22 | 2 | | | | | |
| Explosive properties | | | elf is not explosive with air is possible | | ition of an e | explosible mixture | |
| Dxidising properties | : Pro | duct does n | ot present an oxic | dizing hazard. | | | |
| Particle characteristics | | | • | | | | |

| Code | : 00389122 | Date of issue/Date of revision | : 10 October 2024 |
|---------|-------------------------|--------------------------------|-------------------|
| SANDERS | ON Water Based Eggshell | | |
| | | | |

| SECTION 10: Stability and reactivity | | | | |
|--|--|--|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. | | | |
| 10.2 Chemical stability | : The product is stable. | | | |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. | | | |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition product Refer to protective measures listed in sections 7 and 8. | | | |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. | | | |
| 10.6 Hazardous decomposition products | : Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides | | | |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|----------------------------------|---------------------------------|------------|-----------|----------|
| 7,2-benzisothiazol-3(2H)- | LC50 Inhalation Dusts and | Rat | 0.21 mg/l | 4 hours |
| one | mists | | | |
| | LD50 Oral | Rat | 450 mg/kg | - |
| pyrithione zinc | LC50 Inhalation Dusts and mists | Rat | 0.14 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >2 g/kg | - |
| | LD50 Oral | Rat | 177 mg/kg | - |
| 2-methylisothiazol-3(2H)- one | LC50 Inhalation Dusts and mists | Rat | 0.19 mg/l | 4 hours |
| | LD50 Dermal | Rat | 242 mg/kg | - |
| | LD50 Oral | Rat - Male | 235 mg/kg | - |

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------|------------------|-------------------|--------------------------------|-----------------------------------|--|
| √2-benzisothiazol-3(2H)-one | 450 | N/A | N/A | N/A | 0.21 |
| pyrithione zinc | 221 | N/A | N/A | N/A | 0.14 |
| 2-methylisothiazol-3(2H)-one | 235 | 242 | N/A | N/A | 0.19 |

Irritation/Corrosion

| Product/ingredient name | Resu | lt 👘 | Species | Score | Exposure | Observation |
|------------------------------|--|------------|---------|-------|----------|-------------|
| pyrithione zinc | Eyes - Cornea op | acity Ra | abbit | 4 | 24 hours | 24 hours |
| Conclusion/Summary Skin | Not available. There are no data available on the mixture itself. | | | | | |
| Eyes | There are no data available on the mixture itself. | | | | | |
| Respiratory | : There are no data available on the mixture itself. | | | | | |
| Sensitisation | | | | | | |
| Product/ingredient name | Route of exposure | Speci | es | | Result | |
| 7,2-benzisothiazol-3(2H)-one | skin | Guinea pig | | Sens | sitising | |

| Code : 00389122 SANDERSON Water Bas | | : 10 October 2024 | | | |
|--|---|-------------------|--|--|--|
| SECTION 11: Toxicological information | | | | | |
| Conclusion/Summary | | | | | |
| Skin | There are no data available on the mixture itself | | | | |

| Skin | : There are no data available on the mixture itself. | | | | |
|--|--|--|--|--|--|
| Respiratory | : There are no data available on the mixture itself. | | | | |
| <u>Mutagenicity</u> | | | | | |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | | |
| Carcinogenicity | | | | | |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | | |
| Reproductive toxicity | | | | | |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | | |
| Teratogenicity | | | | | |
| Conclusion/Summary | : There are no data available on the mixture itself. | | | | |
| Specific target organ toxicity (single exposure) | | | | | |

Not available.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| pyrithione zinc | Category 1 | - | - |

Aspiration hazard

Not available.

| Information on likely routes of exposure | : Not available. | | |
|--|--|--|--|
| Potential acute health effects | | | |
| Eye contact | No known significant effects or critical hazards. | | |
| Inhalation | No known significant effects or critical hazards. | | |
| Skin contact | May cause an allergic skin reaction. | | |
| Ingestion | No known significant effects or critical hazards. | | |
| Symptoms related to the phy | cal, chemical and toxicological characteristics | | |
| Eye contact | No specific data. | | |
| Inhalation | No specific data. | | |
| Skin contact | Adverse symptoms may include the following: irritation redness | | |
| Ingestion | No specific data. | | |
| Delayed and immediate effec | as well as chronic effects from short and long-term exposure | | |
| <u>Short term exposure</u> | | | |
| Potential immediate effects | Not available. | | |
| Potential delayed effects | Not available. | | |
| Long term exposure | | | |
| Potential immediate effects | Not available. | | |
| Potential delayed effects | Not available. | | |
| Potential chronic health effe | <u>'S</u> | | |
| Not available. | | | |
| Conclusion/Summary | Not available. | | |
| English (GB) | United Kingdom (UK) | | |

9/15

| Code SANDERS | : 00389122 ON Water Based Eggshell | Date of issue/Date of revision | : 10 October 2024 | |
|---------------------------------------|---------------------------------------|--------------------------------|-------------------|--|
| SECTION 11: Toxicological information | | | | |

| General | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
|-----------------------|---|
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : No known significant effects or critical hazards. |

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|------------------------------|--|--|----------------------|
| 1,2-benzisothiazol-3(2H)-one | Acute EC50 0.11 mg/l | Algae | 72 hours |
| | Acute EC50 2.9 mg/l | Daphnia | 48 hours |
| | Acute LC50 2.15 mg/l | Fish | 96 hours |
| | Chronic NOEC 0.0403 mg/l | Algae - Trout | 72 hours |
| pyrithione zinc | Acute EC50 5.513 µg/l Marine water | Algae - Diatom - Nitzschia | 96 hours |
| | Acute LC50 0.0082 mg/l Chronic NOEC 1.889 μg/l Marine water | <i>pungens</i> Daphnia Algae - Diatom - <i>Nitzschia</i> | 48 hours 96 hours |
| | Chronic NOEC 0.0027 mg/l | <i>pungens</i> Daphnia | 21 days |
| Conclusion/Summary | : Not available. | | |

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | | Dose | Inoculum |
|--|-------------------|----------------|------------------|------|----------------------------|
| pyrithione zinc | - | 39 % - 28 days | | - | - |
| Conclusion/Summary | : Not available. | | | | |
| Product/ingredient name | Aquatic half-life | | Photolysis | 5 | Biodegradability |
| 2-benzisothiazol-3(2H)-one pyrithione zinc | - | | - 50%; < 28 (| | Not readily Not readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|------------------------------|--------|-----|-----------|
| 7,2-benzisothiazol-3(2H)-one | 0.7 | - | Low |
| pyrithione zinc | 0.9 | 0.9 | Low |

12.4 Mobility in soil

| Soil/water partition coefficient (Koc) | : Not available. |
|--|------------------|
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

| Code | : 00389122 | Date of issue/Date of revision | : 10 October 2024 |
|---------|-------------------------|--------------------------------|-------------------|
| SANDERS | ON Water Based Eggshell | | |

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods <u>Product</u> Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

| Waste code | Waste designation | |
|------------|--|--|
| 08 01 12 | waste paint and varnish other than those mentioned in 08 01 11 | |
| Packaging | | |

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | | Waste catalogue |
|---------------------|-------------------------|--|
| Container | 15 01 04 | metallic packaging |
| Special precautions | taken wher Empty con | ial and its container must be disposed of in a safe way. Care should be n handling emptied containers that have not been cleaned or rinsed out. tainers or liners may retain some product residues. Avoid dispersal of al and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | - | | | |
|------------------------------------|-----------------|--|-----------------|-----------------|
| | ADR/RID | ADN | IMDG | ΙΑΤΑ |
| 14.1 UN number | Not regulated. | 9006 | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. | - | - |
| 14.3 Transport hazard class(es) | - | 9 | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. | Not applicable. |

Additional information

ADR/RID : None identified.

ADN : The product is only regulated as a dangerous good when transported in tank vessels.

IMDG : None identified.

IATA : None identified.

| Code : 00389122 SANDERSON Water Based Eg | ashell | Date of issue/Date of revision | 10 October 2024 |
|---|---------------------|--|--------------------------------------|
| SECTION 14: Transpo | | n | |
| 14.6 Special precautions for user | upright and secu | n user's premises: always transporter. Ensure that persons transportin accident or spillage. | |
| 14.7 Transport in bulk according to IMO instruments | : Not available. | | |
| SECTION 15: Regulat | ory informati | on | |
| 15.1 Safety, health and enviro | nmental regulatio | ns/legislation specific for the sub | ostance or mixture |
| <u>UK (GB)/REACH</u> | | | |
| Annex XIV - List of substan | ices subject to aut | <u>horisation</u> | |
| Annex XIV | | | |
| None of the components are | | | |
| Substances of very high c | | | |
| None of the components are | e listed. | | |
| Explosive precursors | : Not applicable. | | |
| Ozone depleting substance | <u>}S</u> | | |
| Not listed. | | | |
| VOC for Ready-for-Use Mixture | | att walls and ceilings (Gloss <25@6 ntains a maximum of 3 g/l VOC. | 0°). EU limit values: 30 g/l (2010.) |
| | | placing on the market and use of | <u>f certain dangerous</u> |
| substances, mixtures and an | <u>rticles</u> | | |
| Product/ingredient name | | | Entry Number (REACH) |
| | Faashell | | 3 |
| ANDERSON Water Based | Eggonen | | |
| ANDERSON Water Based | : Not applicable. | | |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and acronyms | ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group |
|-------------------------------|--|
| | SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification

| Classification | Justification | | |
|--------------------|--------------------|--|--|
| Skin Sens. 1, H317 | Calculation method | | |

Full text of abbreviated H statements

| Code : 00389122 SANDERSON Water Based Eggshell | Date of issue/Date of revision | : 10 October 2024 |
|---|--------------------------------|-------------------|
| SECTION 16: Other information | | |

| H 301 | Toxic if swallowed. |
|--------------|---|
| H302 | Harmful if swallowed. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H360D | May damage the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications

| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
|-------------------|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Repr. 1B | REPRODUCTIVE TOXICITY - Category 1B |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| History | |

| <u></u> | |
|---------------------------------|-------------------|
| Date of issue/ Date of revision | : 10 October 2024 |
| Date of previous issue | : 30 April 2024 |
| Prepared by | : EHS |
| Version | : 1.26 |

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Safe Use of Mixtures Information for end-users

Title

: Professional painting, indoor brush/roller

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor painting by professionals with brush or roller, with good general room ventilation (open doors/windows)

This safe use information is linked to SWED no. : CEPE_PW_04

Product category(ies)

: Coatings and paints, thinners, paint removers

Operational conditions

Place of use

: Indoor use

Risk management measures (RMM)

| • | Maximum | Ventilation | | Respiratory | Eye | Hands | |
|--|----------------------|-------------------------------|----------------------------------|---|--|---------------------------------------|--|
| activity | duration | Туре | ach (air changes per hour) | | | | |
| Preparation of material for application | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. | |
| Loading of application equipment and handling of coated parts before curing | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. | |
| Professional application of coatings and inks by brush or roller | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. | |
| Film formation - force drying, stoving and other technologies | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | ata Sheet for | | |
| Cleaning | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. | |
| Waste management | More than 4 hours | Good general room ventilation | 3 - 5 | See section 8 of this Safety Data Sheet for specifications. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. | |

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

Safe Use of Mixtures Information for end-users

Title

: Professional spray painting, indoor (with respiratory protection)

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

Indoor spray painting by professionals for specialist applications, with good general room ventilation plus respiratory protection

This safe use information is linked to SWED no. : CEPE PW 03b

Product category(ies) : Coatings and paints, thinners, paint removers

Operational conditions

Place of use

: Indoor use Risk management measures (RMM)

Contributing Maximum Ventilation Respiratory Eye Hands activity duration ach (air Type changes per hour) See section 8 of this Safety Wear suitable gloves tested Preparation of material More than Good general 3 - 5 Use eve protection room ventilation Data Sheet for to FN374 for application 4 hours according to EN specifications. 166. Loading of application More than Good general See section 8 of this Safety Use eye Wear suitable gloves tested 3 - 5 equipment and 4 hours room ventilation Data Sheet for protection to EN374. handling of coated according to EN specifications. parts before curing 166. Professional application More than Good general 3 - 5 Wear a respirator Use eye Wear suitable gloves tested protection of coatings and inks by 4 hours room ventilation conforming to EN140 with to EN374. an assigned protection according to EN spraying factor of at least 10. 166. Film formation - force More than Good general 3 - 5 See section 8 of this Safety None None drying, stoving and 4 hours room ventilation Data Sheet for other technologies specifications. More than See section 8 of this Safety Cleaning Good general 3 - 5 Use eve Wear suitable gloves tested protection Data Sheet for 4 hours room ventilation to EN374. specifications. according to EN 166 More than Good general 3 - 5 See section 8 of this Safety Use eye Wear suitable gloves tested Waste management 4 hours room ventilation Data Sheet for protection to FN374 according to EN specifications 166.

See section 8 of this Safety Data Sheet for specifications.



In case this product contains substances classified as hazardous to the environment, the use has been assessed to be safe for the environment. The assessment is based on the exposure parameters that are described for the product use in the corresponding SPERCs. For the disposal of product residues and waste please refer to section 13 of the Safety Data Sheet.

Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document

SANDERSON

It all started in 1900 with a small collection of paints designed to complement the Arthur Sanderson & Sons wallpaper collections. Today, you will find yourself spoilt for choice with Shades of Sanderson – a comprehensive range of paints in a timelessly elegant palette.

WATER BASED EGGSHELL (15815DUT003)

Sanderson Water Based Eggshell is a hard-wearing, water-based paint suitable for interior walls, ceilings, woodwork and suitably primed metalwork. It has a washable, low sheen finish, making it perfect for kitchens, bathrooms and conservatories. Also suitable for use on exterior woodwork and suitably primed metals.

PREPARATION & APPLICATION

Ensure good ventilation during application and drying. All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime bare surfaces with an appropriate Primer. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special Precautions should be taken during surface preparation of

pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Stir well before use. When using more than one tin of the same colour then intermix and stir thoroughly before use. Do not apply in temperatures below 10°C or in damp conditions If more than one can of colour is to be used in the same area, intermix before use.

STORAGE & USE

PROTECT FROM FROST. To avoid risk of spillage, always store and transport in a secure upright position.

AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

| FINISH | APPLICATION | COVERAGE | RECOATABLE AFTER | VOC CONTENT | PRODUCT MAX g/L VOC | EU LIMIT VALUE g/L |
|----------------------|-----------------|----------|---------------------|---------------------|------------------------|-----------------------|
| Water Based Eggshell | Brush or Roller | 12m²/L | 2 - 4 hrs | Minimal 0.1 - 0.29% | 3 | Cat A/a 30 |

HEALTH & SAFETY

Contains 1,2-benzisothiazol-3(2H)-one, and 2-methylisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Keep out of reach of children.

If medical advice is needed, have product container or label at hand. Do not get in eyes, on skin, or on clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.

IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Dispose of contents and container in accordance with all local, regional, national and international regulations. Safety data sheet available on request

Contains biocidal product: BIT, MIT, IPBC

1 Litre e

Voysey House, Sandersons Lane, London, W4 4DS England. Tel: 0203 457 5862 In case of an emergency, please call: 01924 354354 Sanderson Design Group Brands SARL 19 Rue de Mail, 75002 Paris France, T: +33 1 40 41 17 70 Sanderson.SandersonDesignGroup.com/paint/



S176 1227171