

TECHNICAL DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

PRODUCT DETAILS:

BRAND:	Graham & Brown
PRODUCT:	Exterior
DESCRIPTION	A high quality water based exterior eggshell finish emulsion, suitable for prepared / primed wood, metal, uPVC, melamine and masonry surfaces.
USE:	Wood, Metal, Melamine, uPVC, Masonry
CERTIFICATES:	French Indoor Air Class A+



COLOUR:	Available in an exclusive range.
PREPARATION:	Surfaces to be painted must be clean, dry and free from grease, dust and dirt. Bare, untreated timber should be treated with a suitable preservative. Previously painted timber should be sanded prior to painting. Avoid the inhalation of dust. Wear a suitable dust mask if dry sanding and take special precautions when sanding pre-1960's oil based paint surfaces as they may contain harmful lead). Timber or masonry with fungal growth should be treated with a proprietary fungicide prior to application. Ensure any tanalised or creosoted timber is allowed to thoroughly weather before applying. Treat any knots with an appropriate knotting solution. Masonry should be clean, dry and sound prior to painting. If the masonry is powdery it should first be treated with a masonry primer. Previously painted metal should be lightly sanded prior to painting. Bare metal should be primed with a suitable metal primer.
APPLICATION:	Stir thoroughly before use. Suitable for brush or roller application. If more than one can of the same colour is used, ensure the batch numbers are the same or intermix well before use. Two full coats of waterbased Interior Eggshell should be applied to achieve the required colour standard. Average drying time 2-3 hours. Allow a minimum of 12 hours between coats. Allow the coating to fully harden for 7 days before normal use to ensure resistance to knocks and b Stir thoroughly before use. Do not apply in rain or if rain is likely before the paint can fully dry. Apply using a brush. Apply liberally along the grain of the wood. Two full coats of Exterior Eggshell should be applied to give the desired colour and ensure good resistance to weathering. Additional coats may be required on bare timber or where a large colour change is required. Average drying time 2 hours. Allow 5 hours between coats. Hard Dry in 24 hours. Do not apply in temperatures below 8°C, in direct sunlight or if rain is expected.
COVERAGE:	Covers up to 14m ² / litre per coat. The stated coverage is theoretical. The actual coverage depends on the nature and the structure of the surface and the application method.
DRYING:	At 23°C and 65% relative humidity. Touch dry in 1 hour. Can be painted over after approximately 6 hours. Full hardness in 7 days.
AFTERCARE:	Gently wipe soiled areas with a sponge and warm soapy water. Avoid excess local rubbing as this may leave a visible mark when dry. The use of harsh detergents to removes stains is not recommended.

APPLICATION ADVICE:

GENERAL:

- The surface must be capable of supporting the paint completely set, clean, dry and free of dust or grease. Repair cracks and surface irregularities. Remove and/or repair all loose and unstable coats.

EXPOSED / UNTREATED SURFACES:

- Prime highly absorbent surfaces in their entirety with a quality primer/undercoat.
- Thoroughly clean powdery surfaces.
- Prime using a quality primer/undercoat after allowing to dry.
- After drying, apply 2 coats of Graham & Brown Gloss.

PAINTED WALL SURFACES IN GOOD CONDITION:

- Clean thoroughly.
- After drying, apply 2-3 coats of Graham & Brown Gloss.

GRAHAM & BROWN

TECHNICAL DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

EXISTING OLD COATS:

- Remove loose parts.
- Thoroughly wash powdery coats and allow them to dry.
- Carry out repairs.
- Prime with a quality primer/undercoat.
- After drying, apply 2-3 coats of Graham & Brown Gloss.

CONTAMINATION CAUSED BY NICOTINE, DAMP, RUST OR SOOT:

- Clean Thoroughly.
- Treat surfaces / stains with an isolating wall primer.
- After drying, apply 2-3 coats of Graham & Brown Gloss.

WOOD:

- Clean thoroughly.
- Treat bleeding wood with an isolating primer.
- Apply 2-3 coats of Graham & Brown Gloss directly onto the wood.

DISCLAIMER:

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact Graham & Brown Customer Service.

TECHNICAL DATA:

BINDING AGENT: Acrylic Resin

PIGMENTS: Rutile titanium dioxide, mineral fillers, organic and inorganic pigments

SOLVENT: Water

SOLID COMPONENTS: Approx 45% by weight

SPECIFIC GRAVITY: approx 1.24g/cm³

RECOMMENDED COATS: 2 to 3

DEGREE OF GLOSS: Approx 45%

DILUTE WITH: Water

HAZARD CLASSIFICATION: See Safety Data Sheet

TOOL CLEANING INSTRUCTIONS: Use water and soap

STORAGE:

This product is water based and so must be protected from frost and extreme temperatures. To avoid the risk of spillage, always store and transport in a secure and upright position. Use within 6 months of purchase. The manufacturer cannot accept any responsibility for any deterioration of the product or packaging after this time.

GENERAL:

The values stated in this technical data sheet have been determined based on DIN EN 13300. Do not apply at temperatures below 8°C. Only apply if the surface temperature is above 8°C and above the dew point temperature. Always use the required personal protective equipment when applying this product and ensure there is good ventilation when applying. Always read the product label. Safety data sheet is available on request.

SURPLUS PRODUCT:

Dispose of contents / container to waste disposal site in accordance with local / national regulation. Do not empty into drains or watercourses.

GRAHAM & BROWN

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGG SHELL - VARIOUS COLOURS

PAGE: 1

COMPILATION DATE: 15/04/26

REVISION NO. 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER

PRODUCT NAME: GRAHAM & BROWN EXTERIOR EGG SHELL EMULSION - VARIOUS COLOURS

PRODUCT CODE: Various

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

USE OF SUBSTANCE / MIXTURE: PC9a: Coatings and paints, thinners, paint removers.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

COMPANY NAME: Steyport Ltd
Centurion Way
Roman Road Industrial Estate
Roman Road
Blackburn
BB1 2BT

TEL: +44 (0) 1254 583737

FAX: +44 (0) 1254 583839

EMAIL: info@steyport.co.uk



1.4. EMERGENCY TELEPHONE NUMBER

EMERGENCY TEL: +44 (0) 1254 583737 (Office hours only). In case of an emergency telephone 111 or a doctor.

SECTION 2: HAZARDS IDENTIFICATION

2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

CLASSIFICATION UNDER CLP: -: EUH208; -: EUH211 -: EUH210

MOST IMPORTANT ADVERSE EFFECTS: Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.

2.2. LABEL ELEMENTS

LABEL ELEMENTS:

HAZARD STATEMENTS: EUH208: Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH210: Safety data sheet available on request.

PRECAUTIONARY STATEMENTS: P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

- P501:** Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- P262:** Do not get in eyes, on skin, or on clothing.
- P301+P312:** IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- P305+P351+P338:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302:** IF ON SKIN: Gently wash with plenty of soap and water.

2.3. OTHER HAZARDS

PBT: This product is not identified as a PBT/vPvB substance.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. MIXTURES

SECTION 4: FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

SKIN CONTACT: Wash immediately with plenty of soap and water.

EYE CONTACT: Bathe the eye with running water for 15 minutes.

INGESTION: Wash out mouth with water.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

SKIN CONTACT: There may be mild irritation at the site of contact.

EYE CONTACT: There may be irritation and redness.

INGESTION: There may be irritation of the throat.

INHALATION: No symptoms.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

IMMEDIATE / SPECIAL TREATMENT: Protection of First Aiders: No action shall be taken involving any personal risk or without suitable

SECTION 5: FIRE-FIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

EXTINGUISHING MEDIA: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

EXPOSURE HAZARDS: In combustion emits toxic fumes.

5.3. ADVICE FOR FIRE-FIGHTERS

ADVICE FOR FIRE-FIGHTERS: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

PERSONAL PRECAUTIONS: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak- side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. ENVIRONMENTAL PRECAUTIONS

ENVIRONMENTAL PRECAUTIONS: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

CLEAN-UP PROCEDURES: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. REFERENCE TO OTHER SECTIONS

REFERENCE TO OTHER SECTIONS: Refer to section 8 of SDS.

SECTION 7: HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

HANDLING REQUIREMENTS: Not applicable.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

STORAGE CONDITIONS: Store in a cool, well ventilated area. Keep container tightly closed.

SUITABLE PACKAGING: Must only be kept in original packaging.

7.3. SPECIFIC END USE(S)

SPECIFIC END USE(S): No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

WORKPLACE EXPOSURE LIMITS: No data available.

DNEL/PNEC VALUES

DNEL / PNEC: No data available.

8.2. EXPOSURE CONTROLS

ENGINEERING MEASURES: Not applicable.

RESPIRATORY PROTECTION: Respiratory protection not required.

HAND PROTECTION: Protective gloves.

EYE PROTECTION: Safety glasses.

SKIN PROTECTION: Protective clothing.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

STATE:	Liquid		
COLOUR:	Various		
ODOUR:	Characteristic odour		
EVAPORATION RATE:	Slow		
OXIDISING:	Not applicable.		
SOLUBILITY IN WATER:	Miscible in all proportions		
ALSO SOLUBLE IN:	N/A		
VISCOSITY:	Viscous		
KINEMATIC VISCOSITY:	N/A		
VISCOSITY TEST METHOD:	N/A		
BOILING POINT/RANGE°C:	100	MELTING POINT/RANGE°C:	0
FLAMMABILITY LIMITS %:	Not applicable.	UPPER:	Not applicable.
LOWER:		PART.COEFF. N-OCTANOL/WATER:	Not applicable.
FLASH POINT°C:	Not applicable.	VAPOUR PRESSURE:	3.17
AUTOFLAMMABILITY°C:	Not applicable.	PH:	7.5 - 9.5
RELATIVE DENSITY:	1.1 - 1.3		
VOC G/L:	30max		

9.2. OTHER INFORMATION

OTHER INFORMATION: Boiling point, Melting point and Vapour press. data is based upon the following ingredient: water

SECTION 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

REACTIVITY: Stable under recommended transport or storage conditions.

10.2. CHEMICAL STABILITY

CHEMICAL STABILITY: Stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS

HAZARDOUS REACTIONS: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. CONDITIONS TO AVOID

CONDITIONS TO AVOID: Heat.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

10.5. INCOMPATIBLE MATERIALS

MATERIALS TO AVOID: Strong oxidising agents. Strong acids.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

HAZ. DECOMP. PRODUCTS: In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

EXCLUDED HAZARDS FOR SUBSTANCE:

HAZARD	ROUTE	BASIS
Acute toxicity (ac. tox. 4)	-	No hazard: calculated
Acute toxicity (ac. tox. 3)	-	No hazard: calculated
Acute toxicity (ac. tox. 2)	-	No hazard: calculated
Acute toxicity (ac. tox. 1)	-	No hazard: calculated
Skin corrosion/irritation	-	No hazard: calculated
Serious eye damage/irritation	-	No hazard: calculated
Respiratory/skin sensitisation	-	No hazard: calculated
Germ cell mutagenicity	-	No hazard: calculated
Carcinogenicity	-	No hazard: calculated
Reproductive toxicity	-	No hazard: calculated
STOT-single exposure	-	No hazard: calculated
STOT-repeated exposure	-	No hazard: calculated
Aspiration hazard	-	No hazard: calculated

SYMPTOMS / ROUTES OF EXPOSURE

SKIN CONTACT: There may be mild irritation at the site of contact.

EYE CONTACT: There may be irritation and redness.

INGESTION: There may be irritation of the throat.

INHALATION: No symptoms.

SECTION 12: ECOLOGICAL INFORMATION

12.1. TOXICITY

ECOTOXICITY VALUES: No data available.

12.2. PERSISTENCE AND DEGRADABILITY

PERSISTENCE AND DEGRADABILITY: Not biodegradable.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

12.3. BIOACCUMULATIVE POTENTIAL

BIOACCUMULATIVE POTENTIAL: Bioaccumulation potential.

12.4. MOBILITY IN SOIL

MOBILITY: Readily absorbed into soil.

12.5. RESULTS OF PBT AND VPVB ASSESSMENT

PBT IDENTIFICATION: This product is not identified as a PBT/vPvB substance.

12.6. OTHER ADVERSE EFFECTS

OTHER ADVERSE EFFECTS: Toxic to aquatic organisms. Toxic to soil organisms.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

DISPOSAL OPERATIONS: Dispose of contents / container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

RECOVERY OPERATIONS: Not applicable.

DISPOSAL OF PACKAGING: Dispose of contents / container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: TRANSPORT INFORMATION

TRANSPORT CLASS: This product does not require a classification for transport.

SECTION 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

SPECIFIC REGULATIONS: Not applicable.

15.2. CHEMICAL SAFETY ASSESSMENT

SECTION 16: OTHER INFORMATION

OTHER INFORMATION

OTHER INFORMATION: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
* indicates text in the SDS which has changed since the last revision.
This mixture classification has been produced using data provided on the latest version of our sub-contractor's safety data sheets pertaining to the hazardous ingredients contained.

SAFETY DATA SHEET

GRAHAM & BROWN EXTERIOR EGGSHELL - VARIOUS COLOURS

PHRASES USED IN S.2 AND S.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction. EUH211: Warning! Harmful respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH210: Safety data sheet available on request.

LEGAL DISCLAIMER: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

EXTERIOR EGGSHELL

1 LITRE

GRAHAM & BROWN

Printable area for text: 121 x 330

Printable area: 124 x 333

EN BEFORE PAINTING Ensure the surface is smooth, dry and in good condition. Remove any dust, grease and dirt. For untreated wood and hard plastics: pre-treat with a suitable primer such as our Wall Doctor Fixing Primer. For damaged coats of paint: remove and treat as Untreated wood. For any metal: remove rust and pre-treat with a suitable metal primer. Do not use at temperatures below +8°C, in direct sun or when rain is expected. All tins required should be mixed before painting to avoid any colour variation. **WHEN PAINTING** Stir paint thoroughly before use. Apply by brush, roller or paint sprayer. Two coats will usually give good coverage. Sand lightly between coats and make free of dust. In some instances, such as painting over dark colours, additional coats may be required. **AFTER PAINTING** Remove excess paint from tools before cleaning with warm, soapy water. Never empty paint into drains or watercourses. Store leftover paint in a dry place and protect from frost. Dispose of contents/container to hazardous or special waste collection point, in accordance with local regulation. **SAFETY** Contains 1,2-benzisothiazol-3(2H)-one (CAS 2634-33-5), a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (CAS 55965-84-9). May produce an allergic reaction. Warning: Hazardous respirable droplets may be formed when sprayed. Do not breathe the spray or mist. Safety data sheet available on request. If medical advice is needed have product container or label to hand. Keep out of reach of children. Do not get in eyes, on skin or on clothing. **IF SWALLOWED**, call a poison centre or doctor if you feel unwell. **IF ON SKIN**, Gently wash with plenty of soap and water. **IF IN EYES**, rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Keep rinsing.

FR AVANT L'APPLICATION Veillez à ce que la surface soit bien lisse, sèche et en bon état. Pour le bois non traité et les plastiques durs: pré-traiter avec une sous-couche appropriée telle que notre 'Wall Doctor Fixing Primer'. Pour les couches peintes endommagées: enlever les couches de peinture et traiter la surface comme du bois non traité. Pour tout métal: enlever la rouille et appliquer une couche d'apprêt approprié au métal. Ne pas utiliser à des

températures inférieures à +8°C, en plein soleil ou s'il pleut. Le mélange de pots de différentes couleurs doit être fait avant l'application pour éviter les variations de couleur. **PENDANT L'APPLICATION** Mélangez bien la peinture avant utilisation. Appliquez à la brosse, au rouleau ou au pistolet. Il faut généralement deux couches pour une bonne couverture. Poncer légèrement entre les couches et éliminer la poussière. Dans certains cas, par exemple si vous peignez sur des couleurs sombres, des couches supplémentaires peuvent être nécessaires. **APRÈS L'APPLICATION** Enlevez les dépôts de peinture des outils avant de les nettoyer avec de l'eau chaude savonneuse. Ne videz jamais la peinture dans les égouts ou les cours d'eau. Conservez les restes de peinture dans un endroit sec et à l'abri du gel. Jetez les pots dans un centre de collecte des déchets dangereux ou spécialisés, conformément à la réglementation locale. **SÉCURITÉ** Contient 1,2-benzisothiazol-3(2H)-one (CAS 2634-33-5), masse de réaction de 5-chloro-2-méthyl-4-isothiazolin-3-one et de 2-méthyl-2H-isothiazol-3-one (3:1) (CAS 55965-84-9). Peut produire une réaction allergique. Attention! Des gouttelettes respirables dangereuses peuvent se former lors de la pulvérisation. Ne pas respirer les aérosols ni les brouillards. Fiche de données de sécurité disponible sur demande. En cas de consultation d'un médecin, garder à disposition le récipient ou l'étiquette. Tenir hors de portée des enfants. Éviter tout contact avec les yeux, la peau ou les vêtements. **EN CAS D'INGESTION**: Appeler un centre antipoison ou un médecin en cas de malaise. **EN CAS DE CONTACT AVEC LA PEAU**: lavez avec précaution et abondamment à l'eau et au savon. **EN CAS DE CONTACT AVEC LES YEUX**: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.

NL VOOR HET VERVEN Zorg dat het oppervlak glad, droog en in goede staat is. Verwijder stof, vet en vuil. Gebruik voor onbehandeld hout en harde kunststoffen een geschikte primer, zoals onze Wall Doctor Fixing Primer. Voor beschadigde verf lagen: Verwijder en behandel als onbehandeld hout. Voor alle metalen: roest verwijderen en voorbehandelen

met een geschikte metaalprimer. Niet gebruiken bij temperaturen lager dan +8°C, in direct zonlicht of wanneer regen wordt verwacht. Alle benodigde blikken moeten voor het verven worden vermengd om kleurvariatie te voorkomen. **BIJ HET VERVEN** Roer verf grondig door vóór het gebruik. Aanz brengen met een kwast, roller of verfspuit. Twee lagen leveren doorgaans een goede dekking. Licht, pschuren tussen de lagen en stofvrij maken. In sommige gevallen zoals over donkere kleuren kunnen extra lagen nodig zijn. **NA HET VERVEN** Verwijder de overblijvende verf van het gereedschap alvorens te reinigen met warm zeepwater. De verf nooit afvoeren in het riool of waterlopen. Bewaar restjes verf op een droge plaats en bescherm de verf tegen vorst. Voer inhoud/container af naar een afvalinzamelpunt voor gevaarlijk of speciaal afval, in overeenstemming met de plaatselijke regelgeving. **VEILIGHEID** Bevat 1,2-benzisothiazol-3(2H)-on (CAS 2634-33-5), reactiemassa (3:1) van 5-chloor-2-methyl-2H-isothiazol-3-on en 2-methyl-2H-isothiazol-3-on (CAS 55965-84-9). Kan een allergische reactie veroorzaken. Let op! Bij gebruik kunnen gevaarlijke inhalatoire stofdeeltjes worden gevormd. Stof niet inademen. Veiligheidsinformatieblad op verzoek verkrijgbaar. Bij het inwinnen van medisch advies, de verpakking of het etiket ter beschikking houden. Buiten het bereik van kinderen houden. Contact met de ogen, de huid of de kleding vermijden. **NA INSLIKKEN**: bij onwel voelen een **ANTIGIFCENTRUM**/arts raadplegen. **BIJ CONTACT MET DE HUID**: voorzichtig wassen met veel water en zeep. **BIJ CONTACT MET DE OGEN**: voorzichtig afspoelen met water gedurende een aantal minuten; contactlenzen verwijderen, indien mogelijk; blijven spoelen.

DE VOOR DEM STREICHEN Vergewissern Sie sich, dass die Oberfläche glatt, trocken und in gutem Zustand ist. Entfernen Sie jeglichen Staub, Fett und Schmutz. Bei unbehandeltem Holz und Hartkunststoffen: mit einer geeigneten Grundierung vorbehandeln. Bei beschädigten Farbanstrichen: entfernen und wie unbehandeltes Holz behandeln. Für jegliches Metall: Rost entfernen und mit einer geeigneten Metallgrundierung vorbehandeln. Nicht

bei Temperaturen unter +8°C, bei direkter Sonneneinstrahlung oder wenn Regen zu erwarten ist, anwenden. Alle benutzten Dosen sollten vor dem Streichen gemischt werden, um jegliche Farbabweichung zu verhindern. **BEI STREICHEN** Vor Anwendung Farbe gründlich aufrühren. Mit Pinsel, Farbroller oder Spritzpistole auftragen. Zwei Anstriche ergeben normalerweise eine gute Deckung. Zwischen den Anstrichen leicht polieren und frei von Staub machen. Wenn man dunkle Farben übermalt, können weitere Anstriche notwendig sein. **NACH DEM STREICHENT** Überflüssige Farbe von den Werkzeugen entfernen, bevor diese mit warmem Seifenwasser gereinigt werden. Nicht in die Kanalisation oder Wasserläufe gelangen lassen. Nicht verbrauchte Farbe an einem trockenen Ort lagern und vor Frost schützen. Inhalt / Behälter der Problemabfallentsorgung zuführen, gemäß den örtlichen Vorschriften. **SICHERHEIT** Enthält 1,2-Benzisothiazol-3(2H)-on (CAS 2634-33-5), Reaktionsmasse aus 5-Chlor-2-methyl-2H-isothiazol-3-on und 2-Methyl-2H-isothiazol-3-on (3:1) (CAS 55965-84-9). Kann allergische Reaktionen hervorrufen. Achtung! Bei der Verwendung kann gefährlicher lungengängiger Staub entstehen. Staub nicht einatmen. Sicherheitsdatenblatt auf Anfrage erhältlich. Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten. Darf nicht in die Hände von Kindern gelangen. Nicht in die Augen, auf die Haut oder auf die Kleidung gelangen lassen. **BEI VERSCHLUCKEN**: Bei Unwohlsein **GIFTINFORMATIONENZENTRUM**/Arzt anrufen. **BEI KONTAKT MIT DER HAUT**: Sanftsam mit viel Wasser und Seife waschen. **BEI KONTAKT MIT DEN AUGEN**: Einige Minuten lang behutsam mit Wasser spülen. Eventuell vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter spülen.

ES ANTES DE PINTAR Asegúrese de que la superficie esté lisa, seca y en buen estado. Elimine el polvo, la grasa y la suciedad. Para madera sin tratar y plásticos duros: realice un tratamiento previo con una imprimación adecuada, como nuestra imprimación Wall Doctor Fixing Primer. Para capas de pintura dañadas: eliminar y tratar como madera sin tratar. Para cualquier metal: elimine el óxido y realice un tratamiento previo con una imprimación para metal

adecuada. Lijar ligeramente entre manos y eliminar el polvo. No utilizar a temperaturas inferiores a + 8 ° C. Para evitar variaciones del color, se deberán mezclar todas las latas antes de pintar. **AL PINTAR** Mezcle completamente la pintura antes de usar. Aplique con pincel, rodillo o pulverizador de pintura. Dos manos usualmente brindan una buena cobertura. Bajo el sol directo o cuando se espera lluvia. En algunos casos, es posible que se necesiten más colores oscuros, es posible que **PINTAR** Elimine el exceso de pintura de las herramientas antes de limpiarlas con agua jabonosa tibia. No derrame la pintura en drenajes ni cursos de agua. Almacene el remanente de pintura en un lugar seco protegido de la escarcha. Elimine el contenido /contenedor en un punto de recolección de residuos peligrosos o especiales según la normativa local. **SEGURIDAD** Contiene 1,2-Benzisotiazol-3(2H)-ona (CAS 2634-33-5), Masa de reacción de 5-cloro-2-metil-2H-isotiazol-3-ona y 2-metil-2H-isotiazol-3-ona (3:1) (CAS 55965-84-9). Puede provocar una reacción alérgica. Puede provocar una reacción alérgica. Atención! Al utilizarse, puede formarse polvo respirable peligroso. No respirar el polvo. Puede solicitarse la ficha de datos de seguridad. Si se necesita consejo médico, tener a mano el envase o la etiqueta. Mantener fuera del alcance de los niños. Evitar el contacto con los ojos, la piel o la ropa. **EN CASO DE INGESTIÓN**: Llamar a un **CENTRO DE TOXICOLOGÍA**/médico si la persona se encuentra mal. **EN CASO DE CONTACTO CON LA PIEL**: Lavar suavemente con agua y jabón abundante. **EN CASO DE CONTACTO CON LOS OJOS**: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado.



(RECOATABLE IN 4 HOURS)

APPLY COLOUR RECIPE HERE



1 LITRE e
34 fl. oz US / 35 fl. oz UK

+44 (0)1254 691321 grahambrown.com Manufactured in the UK. Graham & Brown, Stanley Street, Blackburn, Lancashire, England BB1 3BW. Graham & Brown B.V., Agriport 99, 1775 TA Middenmeer, Netherlands.